

CME - Ameritek Tabber



- * High Production Tabbing, Labeling and Stamping.
- * Heavy duty construction for reliability and durability.
- * Meet all requirements of owner, operator and USPS.
- * Quick and simple job setups.
- * Microprocessor controlled tab placement.
- * Brushless DC Servo employed for unmatched durability.
- * Wide Head option available for Post-It-Notes, wide labels, and magnets.

TABBING - LABELING - STAMPING

CME - Ameritek Tabber

TECHNICAL SPECIFICATIONS

Configurations

Standard (2") or Wide Head Systems (4½") available.

(as defined by the maximum width of backing material)

Speeds

Production Rates based on 8½" product length.

Single Tab: Up to 30,000 pieces/hour Double Tab: Up to 24,000 pieces/hour Triple Tab: Up to 18,000 pieces/hour

Transport Belt: 0 to 600 feet/minute Tabbing Head: 0 to 375 feet/minute

Application Speeds: Transport belt speeds of 0 to 600 ft/min for tabs < 2" pitch.

Transport belt speeds of 0 to 375 ft/min for tabs > 2" in pitch.

Product Size

Minimum: 3" x 5"
Maximum: 13½" x 17"
Minimum Thickness: 20 # folded sheet
Maximum Thickness: 7/16"

Tabs/ Labels/ Stamps

Self adhesive on roll with 3" core and minimum 1/16" gap between tabs, labels, or stamps.

Minimum Width: ¾" backer width
Maximum Width: 2" backer – Standard
4½" backer – Wide Head

Minimum Pitch: 3/4" Maximum Pitch: 7"

Types: tabs, labels, stamps, repositionable notes, scratch-offs, customized stickers, machine grade paper, clear or translucent. Note: Clear and translucent tabs require an "engineered backer" with printed registration marking for indexing.

*** Magnets possible with optional kit.

Roll Size: Up to $19\frac{1}{2}$ " diameter mounted on a 3" core.

Approximate Roll Capacity: 40,000 – 1" tabs

Tab Placement

Accuracy: +/- 1/8" repeatability

Physical Size

System Length: 37" System Width: 33" System Height: 71"

Tabletop Height: 32¾ to 35" - Standard

35¾" to 38" - Optional

Weight: Approximately 450 lbs.

Electrical Requirements

115 VAC 50/60 Hz @ 10 Amps or 230 VAC 50/60 Hz @ 5 Amps

The CME - Ameritek Tabber applies tabs, labels, stamps, repositionable post-it notes, and scratch-offs to a wide variety of media including tri-fold brochures, newsletters, small catalogs and many others. It is designed for professional mailers, commercial printers, fulfillment houses or anyone else requiring a heavy-duty high quality Tabber/Labeler/Stamp Affixer. It has front panel controls that are easy to use, making it simple to set up jobs or to switch between applications.

The CME- Ameritek Tabber can be used in-line with most friction feeders, inkjet print systems, conveyors and even some folders. It can also be run offline with a feeder in stand-alone operation.



The CME- Ameritek Tabber can also be configured as a Dual Headed Tabber. This system can tab on the leading (toe) and trailing (heel) edges of a booklet in a single pass. The Dual Headed Tabber can run in-line or off-line as a system, or the Tabbers can be unlocked and used as stand-alone units.



Capital Mailing Equipment Inc.

New-Pre-Owned-Supplies

833-263-6245