



(763) 502-0000 www.streamfeeder.com info@streamfeeder.com

Tip-on / Attaching Series Streamfeeder Converge C-900 and C-1200 Tip-on Feeders

Overview

The Converge Series Tip-on Feeders are designed to be a modular, high-speed accurate placing feeder. Precision placement of products onto carrier targets is performed consistently and accurately at high speed. The modular design allows Converge feeders to be easily integrated to existing equipment such as folder/gluers, vacuum bases, conveyors, or configured as part of a turn-key attaching system.

Feed a wide variety of flat and multi-thickness products including cards, coupon, and more up to 24,000 pieces per hour (business card).

Standard Features

Long lasting natural gum rubber feed belt with vacuum assist ready • One-knob side guide adjust • Adjustable discharge angle • Servo motor/controller • Encoder • Pushbutton operator interface • Universal mount for most bases • Stainless steel construction • High performance product sensor • System I/O interface • Variable adjust placement position • Discharge guides to ensure side-to-side registration • No-adjust hold-down

Applications (ask us about your application)			
Mailing Systems	Flighted Infeeds	Conveyors	
Vacuum Transports	Folders/Gluers	Box Packaging	
Products (askus should			
Products (ask us about your products)			
Plastic Cards	Collapsed Cartons	Folded Documents	
Manuals	Coupons	Magnets	
Cardstock	Envelopes	Booklets	
Backer Board	Business Cards	and more	

24" Tall Stainless Steel Side Guides		
Durable Stainless Steel Construction	One-K	nob Side Guide Adjust
Long-Lasting Gum Rubber Feed Belts and Vacuum Assist Ready	Pa	tented Product Separator
XIT		Adjustable Angle Discharge
Universal Mounting Kit Si Disch	elf-Adjusting arge Hold-Down	Alignment Guides

Specifications	
Maximum Product Size	C-900: 7 W x 6 L in (178 x 153 mm) C-1200: 10 W x 10 L in (254 x 254 mm)
Minimum Product Size	2 W x 2.5 L in (51 x 64 mm)
Min/Max Product Thickness	.003250 in (.076 - 6.35 mm)
Belt Speed	4000 in/min (102 m/min)
Utilities	115/230vac, 50/60Hz, 3A
Weight	Feeder: 62 lbs. (28 kg) Enclosure: 45 lbs. (21 kg)
Warranty	One year limited
Other sizes and thickness ca	apabilities available. Contact us for your application.

FOOTPRINT DRAWING AVAILABLE AT: www.streamfeeder.com/footprints.html or scan the QR Code





Streamfeeder

NIGRELLI

Hudson-Sharp Salv



