



(763) 502-0000 WWW.STREAMFEEDER.COM INFO@STREAMFEEDER.COM

Labeling Series Streamfeeder V-1000p Continuous Feeder

Overview

The V-1000p is designed to feed flat and multi-thickness products continuously into production streams with exceptional alignment qualities. Perfect for lower speed applications where consistent feeding is required such as laminating and reinforcing. The importance of straight feeding and minimizing skewing can help improve label placement accuracy, consistent bar code reading, alignment of products, and more importantly, increased efficiency.


Feed a wide variety of flat and multi-thickness products into production streams for printing, coding, labeling, tabbing, laminating, and more.

Standard Features

Repositionable feed belts • Independent side guide positioning · Extended guide rails all the way through the feeder · Two independent adjustable product separators • Long lasting natural gum rubber feed belts · Variable speed control · Maintenance-free stepper motor Universal external run interface kit

Applications (ask us about your application)				
Addressing	Laminating	Printing		
Labeling	Tabbing	Reinforcing		
Scanning	Coding			
Products (ask us abo	ut your products)			
Sheet Paper	Backer Board	Folded Documents		

Sheet Paper	Backer Board	Folded Documents
Manuals	Collapsed Cartons	Folders
Cardstock	Envelopes	Booklets
Post Cards	Brochures	and more



ugn	uio	100	uoi	10	1000
pro	duc	ts s	trai	ghi	t

Specifications	
Maximum Product Size	12 W x 18 L in (305 x 457 mm)
Minimum Product Size	2.5 W x 3.0 L in (63.5 x 76.2 mm)
Min/Max Product Thickness	.003 - 1.00in (.076 - 25.4 mm)
Belt Speed	2950 in/min (75 m/min)
Utilities	115vac, 60Hz, 3A
Weight	47 lbs. (21.3 kg)
Warranty	Two year limited
Other sizes and thickness c	apabilities available. Contact us for your application.

FOOTPRINT DRAWING AVAILABLE AT: www.streamfeeder.com/footprints.html or scan the QR Code





Streamfeeder

NIGRELLI

HUDSON-SHARP



