KR 533 Autoloader





Automatic Hopper Loader



Improve feeder consistency and productivity with the new KR 533 Autoloader. The KR 533 handles a wide variety of product and is versatile enough to work with almost any feed system.

The KR 533 manages nearly 6' of material and delivers it into the hopper as needed. The hopper level is maintained within a narrow range keeping the feed consistent. The KR 533's jogger assembly keeps product straight in the hopper.

The only autoloader designed to work with friction and shuttle feeders, the KR 533 keeps you flexible. Slotted brackets allow the top to be quickly angled for friction feeders or placed horizontal for shuttle feeders. You can also use the KR 533 inline or 90 degrees to product flow.

If you're looking for cost effective, flexible solutions to improve productivity, look no further than the KR 533.



The KR 533 can be used with friction feeders. as well as shuttle feeders.

KR 533 Autoloader Automatic Hopper Loader

General Specifications

<u>Physical</u>

Length 69" Height 36" Width 20"

Electrical Requirements

Voltage 120 VAC Current 15 amps Phase single Hertz 60

Production Rate

Belt speed 100 ft/min

Material Handling

Min stock size 3" x 5" Max stock size 9" x 12"

Minimum stock thickness single sheet

Maximum stock thickness 1/4"

Features


67" belted conveyor
Variable speed DC motor
Telescoping conveyor top
Conveyor top angle adjustment
Stack height sensor
Jogger to condition product in the hopper
Hydraulic lift kit for quick installation

Options

Longer units available

Your Kirk-Rudy dealer is:






You don't need to buy another friction feeder with the KR 533. Angled brackets allow you to rotate the KR 533 matching the angle of your friction feeder.



Adjust the table to a horizontal position and use the KR 533 with your shuttle feeder.



The KR 533's jogger assembly conditions material in the hopper improving feeder consistency