KR224DMShuttle Feeder



This stand alone shuttle feeder is capable of handling a wide variety of media from single sheets and envelopes to books and magazines.

Feeds

just about

everything

- Dual Motor, variable speed
- Jam detect skid bar
- Continuous, consistent feeds
- Oil-less high volume vacuum pump

Top loading, bottom feeding for continuous operation

- √ Heavy Duty
- ✓ Fast
- ✓ Reliable







KR224DM

Shuttle Feeder

Consistently feeds a wide assortment of product.

FEATURES:

- Fully adjustable guides
- · Jam detect skid bar
- Interchangeable vacuum plates
- Oil-less high volume vacuum pump
- Semi-automatic manual lubrication system
- Easy belt changes

OPTIONS:

- Extra wide version (up to 30" wide product)
- Clutch/brake control (with predermined counter)



Adjustable feed rollers and vacuum plate.

** General Specifications

Product Capacity

Width	Min 3" (7.6 cm)	Max 17" (43.2 cm)
Length	Min 5" (12.7 cm)	Max 17" (40.6 cm)
Thickness	Min .007" (.10 mm)	Max .625" (15.9 mm)

Operating Speeds

Maximum	Variable to 30,000 cycles/hour
---------	--------------------------------

Note: Speeds are dependent on material being fed

Physical English		Metric	
Length	43.20"	109.7 cm	
Width	31.175"	79.2 cm	
Height	33.25"	84.5 cm	
Weight	480 lbs.	218 kg.	

Electrical Requirements

Motors	Voltage	Amp	Phase	Hz
2 - ½ HP	220 VAC	15	1	60



**Specifications subject to change without notice.

